

Air micro-plasmas generated by surface-waves in capillary tubes: spectroscopic diagnostics and kinetic modelling

P Coche⁴ (*), V. Guerra⁴, L.L. Alves⁴, O. Leroy¹, G.D. Stancu^{2,3}, P. Leprince¹, T. Minea¹

¹CNRS, UMR 8578, LPGP, Université Paris-Sud XI, 91405 Orsay, France

²CNRS, UPR 288, EM2C, Grande Voie des Vignes, 92290 Châtenay-Malabry, France

³Ecole Centrale Paris, Grande Voie des Vignes, 92290 Châtenay-Malabry, France

⁴Instituto de Plasmas e Fusão Nuclear, Instituto Superior Técnico, Universidade de Lisboa, Lisboa, Portugal

(*) philippe.coche@tecnico.ulisboa.pt

The research in micro-plasma sources has known a growing interest over the last years due to applications in several fields, such as photonics with the development of powerful UV sources, environment for the decontamination of organic material and biomedicine aiming the production of chemically active species, especially if the plasma is produced under controlled microfluidics flow conditions [1]. The use of microwaves is also an interesting choice, to achieve outstanding power transfer.

This work studies CW-microwave (2.45 GHz frequency) micro-plasmas, produced within a capillary (690 μ m inner diameter) in dry air (N₂ 80% : O₂ 20%), at ~100 W coupled power and constant ~2 mbar pressure. The capillary is inserted into a surfatron, creating stable plasmas with ~3 cm length [2]. The plasmas are characterized using both diagnostics and modelling. State-of-the-art spatially-resolved (axially and radially) spectroscopic techniques are used to measure the line / band radiative emissions with H β , N₂(B), N₂(C), N₂⁺, N* and O* to obtain the electron density n_e , the gas rotational temperature T_{rot} and vibrational temperature T_{vib} , and the absolute densities of the most relevant excited species. The measured quantities are used either as input parameters or for model validation.

Modelling uses a self-consistent hybrid approach that couples the homogeneous two-term electron Boltzmann equation to a set of 0D rate balance equations for the main neutral / charged species. A comprehensive kinetic scheme [3] is adopted in the model, considering the different collisional-radiative mechanisms with the complex atomic/molecular gas/plasma system and accounting for the evolution of the mixture composition due to the dissociation of species at constant pressure. The maintenance reduced electric field is calculated as eigenvalue solution to the problem, so as to satisfy the charged-particle gain-loss rate balance.

Results reveal a high-density non-equilibrium plasma, featuring $T_{rot} \sim (700 - 1100) \pm 100$ K and $T_{vib} \sim (50000 - 55000) \pm 1000$ K for $n_e \sim 10^{13}$ cm⁻³. Discussion will analyse the production of species with these plasmas, considering the importance of the electron kinetics and focusing on the dissociation and ionisation degrees obtained.

Work partially supported by LaSIPS excellence laboratory (Project MicroCap) and by Fundação para a Ciência e a Tecnologia (FCT) (Project Pest-OE/SADG/LA0010/2011).

[1] S. Dap, O. Leroy, J. Andrieu, G.D. Stancu, M. Simeni Simeni, C. Boisse-Laporte, P. Leprince, C.O. Laux, T. Minea, *International Vacuum Conference - IVC-19* (2013) Paris, France

[2] S. Dap, G.D. Stancu, O. Leroy, C. Boisse-Laporte, P. Leprince, T. Minea, *31st International Conference on Phenomena in Ionized Gases – ICPIG* (2013) Granada, Spain

[3] V. Guerra and J. Loureiro, *Plasma Sources Sci. Technol.* **8** (1999) 110